

LARNE PORT

Larne Port Quay Details – Dec 22

Quay	Curran	Olderfleet	MacKean	Chaine	Continental
Max Vessel Length after Specific Risk Assessments	185m	70m	180m	130m	135m
Solid Quay Length	90m	65m	130m	90m	90m
Depth alongside	7.1m	5.1m	6.5m	6.1m	5.5m
Height of Quay above Chart Datum	5.8m Top of fender 7.4m	5.6m	5.6m	5.6m	5.6m
Fresh Water Delivery 14t/hr	Yes	Yes	Yes	Yes	Yes
Cargo Handling	Suitable for Heavy lift operations Ground load: 18t/m2. 1000t crane can use this quay	Suitable for bulk cargoes.	Currently exclusively used by P&O	Used for fuel transfers, Passenger and Crew changes. Limited Lifting Operations.	Suitable for bulk cargoes. Weight limits apply. 10t/m2 but 3T/m2 within 10m of quay edge
Ramp technical details					
Total Width	10.75m	N/A	10.5m	7.85m	7.8m
Centre Line	5.375m	N/A	5.25m	3.92m	3.9m
Edge of Ramp to fender face	5.0m	N/A	5.4m	6.85m	6.2m
Centre line to fender face	10.375m	N/A	10.65m	10.77m	10.1m
SWL	180t	N/A	180t	180t	180t
Decks	Single	N/A	Double	Double	Double